

M A T E R I A L S A F E T Y D A T A S H E E T

POLYSEAL FLOOR FINISH-AMBER GLOSS

Page: 1

PRODUCT NAME: POLYSEAL FLOOR FINISH-AMBER GLOSS
PRODUCT CODE: 89-3455

HMIS CODES: H F R P
2 1 1 B

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: CONTINENTAL PRODUCTS COMPANY
ADDRESS : 1150 East 222 Street
Euclid, OH 44117

EMERGENCY PHONE : (800)255-3924 **DATE PRINTED** : 01/22/03
INFORMATION PHONE : (216)531-0710 **NAME OF PREPARER** : John Stevens

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBR	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
Water (nonhazardous) ACGIH TLV: Not Established OSHA PEL: Not Established	7732-18-5		62
+ DIPROPYLENE GLYCOL METHYL ETHER ACGIH TLV: 100 ppm; 606 mg/M3 (Skin TWA); 150 ppm; 909 mg/M3 (STBL) OSHA PEL: 100 ppm; 600 mg/M3	34590-94-8		11.2
+* N-METHYL-2-PYRROLIDONE ACGIH TLV: Not Established OSHA PEL: Not Established	872-50-4		3.3

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
+ indicates toxic chemical(s) subject to the reporting requirements of section 311 and 312 of Title III and of 40 CFR 372.
Indicates a Chronic hazard. See warning (if applicable) in Section IX.
CONTACT CONTINENTAL PRODUCTS COMPANY IF CALIFORNIA PROPOSITION 65 INFORMATION IS NEEDED.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING RANGE: 212 F - 364 F **SPECIFIC GRAVITY (H2O=1):** 1.02
VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
V.O.C. (less water): 2.32 lb/gl **MATERIAL V.O.C. :** 1.01 lb/gl
SOLUBILITY IN WATER: READILY SOLUBLE
APPEARANCE : AMBER LIQUID **ODOR:** CHARACTERISTIC PAINT ODOR

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASHPOINT : > 200 DEG. F. SETA **METHOD USED:** SETAFLASH
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a
EXTINGUISHING MEDIA: Carbon Dioxide, dry chemical or foam. If water, fog nozzles preferred.

SPECIAL FIREFIGHTING PROCEDURES
Water may be used to cool closed containers to prevent pressure build-up when exposed to extreme heat. Firefighting personnel should wear self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode (due to the build-up of steam pressure) when exposed to extreme heat.

=====**SECTION V - REACTIVITY DATA**=====

M A T E R I A L S A F E T Y D A T A S H E E T

POLYSEAL FLOOR FINISH-AMBER GLOSS

Page: 2

STABILITY: Stable
CONDITIONS TO AVOID

Heat, sparks, open flame and fire. Material is subject to freezing. Do not store above 120 Degrees Fahrenheit.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

BY FIRE: Normal products of incomplete combustion. May produce fumes when heated to decomposition, as in welding. Fumes may contain carbon monoxide/dioxide or oxides of nitrogen.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

THRESHOLD LIMIT VALUE: SEE SECTION II

PRIMARY ROUTE(S) OF ENTRY:

Inhalation and skin contact.

EFFECTS OF OVEREXPOSURE:

May cause headache, nausea, eye or skin irritation. (Material is slightly alkaline.)

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Repeated exposure to emitted vapors may cause irritation to the upper respiratory tract. Preexisting skin sensitization may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. Administer artificial respiration or oxygen if breathing is difficult. Call for prompt medical attention. **EYES:** Flush immediately with large amounts of water for at least 15 minutes. Get medical attention. **SKIN:** Wash affected area with soap and water. Remove and launder contaminated clothing. Consult a physician if irritation persists. **INGESTION:** Do not induce vomiting. Keep at rest. Call a physician immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area. Ventilate area if necessary. Recover free liquid by addition of inert absorbent to spill area. Sweep up and place material in a suitable disposal container. Wash down spill area with copius quantities of water.

WASTE DISPOSAL METHOD

Disposal must be made in accordance with Local, State, and Federal regulations. Incineration or landfilling must be in an approved facility. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store out of the sun and away from heat, sparks, and open flame. Keep containers closed and upright to prevent leakage. Do not store below 40 Degrees Fahrenheit or above 120 Degrees Fahrenheit for extended periods. Do not reuse product container for any purpose.

OTHER PRECAUTIONS

Do not get in eyes. Avoid skin contact. Do not take internally. Prevent prolonged or repeated breathing of vapor or spray mist. Keep out of reach of children.

===== SECTION VIII - CONTROL MEASURES =====

M A T E R I A L S A F E T Y D A T A S H E E T

POLYSEAL FLOOR FINISH-AMBER GLOSS

Page: 3

RESPIRATORY PROTECTION

Observe the OSHA Respiratory Protection Standard (29 CFR 1910.134) for respirator selection and use. Selection of the most appropriate respirator will depend on the specific work environment and should be made only by a person familiar with the working conditions and with the benefits and limitations of respiratory protection products.

VENTILATION

Ventilation should dilute to below LEL and TLV to be considered adequate. All applications areas should be ventilated in accordance with the applicable regulations found in 29 CFR, Part 1910.

Respiratory protection should be provided in accordance with 29 CFR, Part 1910.134.

PROTECTIVE GLOVES

Recommended if skin contact is likely.

EYE PROTECTION

Chemical goggles or safety eyewear with splash shields is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Suitable barrier cremes, impervious clothing and boots are recommended to reduce repeated contact with material and limit contamination.

WORK/HYGIENIC PRACTICES

Wash hands with soap and water before eating or using the washroom. Smoke in smoking areas only. Remove and wash contaminated clothing before reuse.

===== SECTION IX - REGULATORY AND ADDITIONAL HAZARDS INFORMATION =====

All components of this product are listed in the TSCA inventory.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRENTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION ABOVE.