

M A T E R I A L   S A F E T Y   D A T A   S H E E T

WEATHERSEAL EXT WOOD FINISH, CANYON BRN

Page: 1

PRODUCT NAME: WEATHERSEAL EXT WOOD FINISH, CANYON BRN
PRODUCT CODE: 82-4243-I-04

HMIS CODES: H F R P
2 2 1 G

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CONTINENTAL PRODUCTS COMPANY
ADDRESS : 1150 East 222 Street
Euclid, OH 44117

EMERGENCY PHONE : (800)255-3924 DATE PRINTED : 01/13/05
INFORMATION PHONE : (216)531-0710 NAME OF PREPARER : John Stevens

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP), and WEIGHT PERCENT. Rows include Water, STODDARD SOLVENT, LINSEED OIL, DISODIUM OCTABORATE TETRAHYDRATE, HYDRATED MAGNESIUM SILICATE, Talc, SOAPSTONE, Proprietary HYDROCARBON WAX, CALCIUM NAPHTHENATE, AROMATIC PETROLEUM DISTILLATES, HI-SOL 10, COBALT 2-Ethylhexoate/Neodecanoate, and SILICA.

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
+ indicates toxic chemical(s) subject to the reporting requirements of section 311 and 312 of Title III and of 40 CFR 372.
# Indicates a Chronic hazard. See warning in Section IX.
CONTACT CONTINENTAL PRODUCTS COMPANY IF CALIFORNIA PROPOSITION 65 INFORMATION IS NEEDED.



**M A T E R I A L   S A F E T Y   D A T A   S H E E T**

**WEATHERSEAL EXT WOOD FINISH, CANYON BRN**

**Page: 3**

**INHALATION:** Remove to fresh air. Administer artificial respiration or oxygen if breathing is difficult. Call for prompt medical attention. **EYES:** Flush immediately with large amounts of water for at least 15 minutes. Get medical attention. **SKIN:** Wash affected area with soap and water. Remove and launder contaminated clothing. Consult a physician if irritation persists. **INGESTION:** Do not induce vomiting. Keep at rest. Call a physician immediately.

**===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Dike spill area. Ventilate area if necessary. Recover free liquid by addition of inert absorbent to spill area. Sweep up and place material in a suitable disposal container. Wash down spill area with copius quantities of water.

**WASTE DISPOSAL METHOD**

Disposal must be made in accordance with Local, State, and Federal regulations. Incineration or landfilling must be in an approved facility. Do not incinerate closed containers.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store out of the sun and away from heat, sparks, and open flame. Keep containers closed and upright to prevent leakage. Do not store below 40 Degrees Fahrenheit or above 120 Degrees Fahrenheit for extended periods. Do not reuse product container for any purpose.

**OTHER PRECAUTIONS**

Do not get in eyes. Avoid skin contact. Do not take internally. Containers should be grounded when pouring. Prevent prolonged or repeated breathing of vapor or spray mist. Keep out of reach of children. This material is electrically conductive. Do not apply by electrostatic spray equipment unless the equipment is modified and intended for the application of conductive coatings.

**===== SECTION VIII - CONTROL MEASURES =====**

**RESPIRATORY PROTECTION**

Observe the OSHA Respiratory Protection Standard (29 CFR 1910.134) for respirator selection and use. Selection of the most appropriate respirator will depend on the specific work environment and should be made only by a person familiar with the working conditions and with the benefits and limitations of respiratory protection products.

**VENTILATION**

Ventilation should dilute to below LEL and TLV to be considered adequate. All applications areas should be ventilated in accordance with the applicable regulations found in 29 CFR, Part 1910.

Respiratory protection should be provided in accordance with 29 CFR, Part 1910.134.

**PROTECTIVE GLOVES**

Recommended if skin contact is likely.

**EYE PROTECTION**

Chemical goggles or safety eyewear with splash shields is recommended.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Suitable barrier cremes, impervious clothing and boots are recommended to reduce repeated contact with material and limit contamination.

**WORK/HYGIENIC PRACTICES**

Wash hands with soap and water before eating or using the washroom. Smoke in smoking areas only. Remove and wash contaminated clothing before reuse.

**===== SECTION IX - REGULATORY AND ADDITIONAL HAZARDS INFORMATION =====**

Cobalt Compounds - IARC concludes there is inadequate evidence for the carcinogenicity of cobalt and cobalt compounds in humans and sufficient evidence for the carcinogenicity of cobalt and cobalt compounds in experimental animals. IARC's overall evaluation is that cobalt compounds are possibly carcinogenic to humans (Group 2B). (IARC Monographs VOL 52(1991) COBALT AND COBALT COMPOUNDS)

**M A T E R I A L   S A F E T Y   D A T A   S H E E T**

**WEATHERSEAL EXT WOOD FINISH, CANYON BRN**

**Page: 4**

Silica (Crystalline) - IARC has concluded that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1). (IARC Monographs VOL 68(1997) SILICA)  
NTP lists crystalline silica as reasonably anticipated to be a human carcinogen.

All components used in the manufacture of this product are listed in the TSCA inventory.  
THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER NO GUARANTY OR WARRENTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION ABOVE.