

M A T E R I A L S A F E T Y D A T A S H E E T

WEATHERSEAL EXT WOOD FINISH, APACHE BRN

Page: 1

PRODUCT NAME: WEATHERSEAL EXT WOOD FINISH, APACHE BRN
PRODUCT CODE: 82-4307-I-04

HMIS CODES: H F R P
2 2 1 G

**=====
SECTION I - MANUFACTURER IDENTIFICATION
=====**

MANUFACTURER'S NAME: CONTINENTAL PRODUCTS COMPANY
ADDRESS : 1150 East 222 Street
Euclid, OH 44117

EMERGENCY PHONE : (800)255-3924 **DATE PRINTED :** 01/13/05
INFORMATION PHONE : (216)531-0710 **NAME OF PREPARER :** John Stevens

**=====
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION
=====**

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
Water (nonhazardous) ACGIH TLV: Not Established OSHA PEL: Not Established	7732-18-5		47
+ STODDARD SOLVENT ACGIH TLV: 100 ppm; 525 mg/M3 (TWA) OSHA PEL: 500 ppm; 2000 mg/M3	64742-88-7		10.6
LINSEED OIL ACGIH TLV: Not Established; OSHA PEL: Not Established DANGER-Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly disposed. Immediately after each use, place rags, steel wool or waste in a sealed water-filled metal container. Used spray booth filters should be handled with the same care.	67746-08-1		7.0
DISODIUM OCTABORATE TETRAHYDRATE ACGIH TLV: 3mg/M3 Respirable OSHA PEL: 5mg/M3 Respirable; 15mg/M3 Total	12008-41-2		3.4
HYDRATED MAGNESIUM SILICATE; TALC; SOAPSTONE ACGIH TLV: 6 mg/M3 (Total TWA); 2 mg/M3 (Respirable TWA) OSHA PEL: 20 Mppcf	14807-96-6		3.1
+ Proprietary HYDROCARBON WAX ACGIH TLV: Not Established OSHA PEL: Not Established	Wax Mixture		3
CALCIUM NAPHTHENATE ACGIH TLV: Not Established OSHA PEL: Not Established	61789-36-4		1.4
# COBALT 2-Ethylhexoate/Neodecanoate ACGIH TLV: 0.02 mg/M3 (elemental and inorganic as Co TWA) OSHA PEL: 0.1 mg/M3 (metal, dust, fume as Co)	7440-48-4		0.12854

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
+ indicates toxic chemical(s) subject to the reporting requirements of section 311 and 312 of Title III and of 40 CFR 372.
Indicates a Chronic hazard. See warning in Section IX.
CONTACT CONTINENTAL PRODUCTS COMPANY IF CALIFORNIA PROPOSITION 65 INFORMATION IS NEEDED.

**=====
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
=====**

BOILING RANGE: 212 F - 380 F **SPECIFIC GRAVITY (H2O=1):** 1.01
VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
V.O.C. (less water): 2.06 lb/gl **MATERIAL V.O.C. :** 1.09 lb/gl
SOLUBILITY IN WATER: READILY SOLUBLE
APPEARANCE : BROWN LIQUID **ODOR:** CHARACTERISTIC PAINT ODOR

M A T E R I A L S A F E T Y D A T A S H E E T

WEATHERSEAL EXT WOOD FINISH, APACHE BRN

Page: 3

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area. Ventilate area if necessary. Recover free liquid by addition of inert absorbent to spill area. Sweep up and place material in a suitable disposal container. Wash down spill area with copious quantities of water.

WASTE DISPOSAL METHOD

Disposal must be made in accordance with Local, State, and Federal regulations. Incineration or landfilling must be in an approved facility. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store out of the sun and away from heat, sparks, and open flame. Keep containers closed and upright to prevent leakage. Do not store below 40 Degrees Fahrenheit or above 120 Degrees Fahrenheit for extended periods. Do not reuse product container for any purpose.

OTHER PRECAUTIONS

Do not get in eyes. Avoid skin contact. Do not take internally. Containers should be grounded when pouring. Prevent prolonged or repeated breathing of vapor or spray mist. Keep out of reach of children. This material is electrically conductive. Do not apply by electrostatic spray equipment unless the equipment is modified and intended for the application of conductive coatings.

===== **SECTION VIII - CONTROL MEASURES** =====

RESPIRATORY PROTECTION

Observe the OSHA Respiratory Protection Standard (29 CFR 1910.134) for respirator selection and use. Selection of the most appropriate respirator will depend on the specific work environment and should be made only by a person familiar with the working conditions and with the benefits and limitations of respiratory protection products.

VENTILATION

Ventilation should dilute to below LEL and TLV to be considered adequate. All applications areas should be ventilated in accordance with the applicable regulations found in 29 CFR, Part 1910. Respiratory protection should be provided in accordance with 29 CFR, Part 1910.134.

PROTECTIVE GLOVES

Recommended if skin contact is likely.

EYE PROTECTION

Chemical goggles or safety eyewear with splash shields is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Suitable barrier cremes, impervious clothing and boots are recommended to reduce repeated contact with material and limit contamination.

WORK/HYGIENIC PRACTICES

Wash hands with soap and water before eating or using the washroom. Smoke in smoking areas only. Remove and wash contaminated clothing before reuse.

===== **SECTION IX - REGULATORY AND ADDITIONAL HAZARDS INFORMATION** =====

Cobalt Compounds - IARC concludes there is inadequate evidence for the carcinogenicity of cobalt and cobalt compounds in humans and sufficient evidence for the carcinogenicity of cobalt and cobalt compounds in experimental animals. IARC's overall evaluation is that cobalt compounds are possibly carcinogenic to humans (Group 2B). (IARC Monographs VOL 52(1991) COBALT AND COBALT COMPOUNDS)

All components used in the manufacture of this product are listed in the TSCA inventory.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER NO GUARANTY OR WARRENTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION ABOVE.