

M A T E R I A L   S A F E T Y   D A T A   S H E E T

WEATHERSEAL EXT WOOD FINISH, BUCKSKIN

Page: 1

PRODUCT NAME: WEATHERSEAL EXT WOOD FINISH, BUCKSKIN
PRODUCT CODE: 82-4368-I-04

HMIS CODES: H F R P
2 2 1 G

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CONTINENTAL PRODUCTS COMPANY
ADDRESS : 1150 East 222 Street
Euclid, OH 44117

EMERGENCY PHONE : (800)255-3924 DATE PRINTED : 01/13/05
INFORMATION PHONE : (216)531-0710 NAME OF PREPARER : John Stevens

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE mm Hg @ TEMP, WEIGHT PERCENT. Rows include Water, STODDARD SOLVENT, LINSEED OIL, DISODIUM OCTABORATE TETRAHYDRATE, HYDRATED MAGNESIUM SILICATE; TALC; SOAPSTONE, Proprietary HYDROCARBON WAX, and COBALT 2-Ethylhexoate/Neodecanoate.

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
+ indicates toxic chemical(s) subject to the reporting requirements of section 311 and 312 of Title III and of 40 CFR 372.
# Indicates a Chronic hazard. See warning in Section IX.

CONTACT CONTINENTAL PRODUCTS COMPANY IF CALIFORNIA PROPOSITION 65 INFORMATION IS NEEDED.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 F - 300 F SPECIFIC GRAVITY (H2O=1): 1.01
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
V.O.C. (less water): 2.06 lb/gl MATERIAL V.O.C. : 1.10 lb/gl
SOLUBILITY IN WATER: READILY SOLUBLE
APPEARANCE : BROWN LIQUID ODOR: CHARACTERISTIC PAINT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA



**WASTE DISPOSAL METHOD**

Disposal must be made in accordance with Local, State, and Federal regulations. Incineration or landfilling must be in an approved facility. Do not incinerate closed containers.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store out of the sun and away from heat, sparks, and open flame. Keep containers closed and upright to prevent leakage. Do not store below 40 Degrees Fahrenheit or above 120 Degrees Fahrenheit for extended periods. Do not reuse product container for any purpose.

**OTHER PRECAUTIONS**

Do not get in eyes. Avoid skin contact. Do not take internally. Containers should be grounded when pouring. Prevent prolonged or repeated breathing of vapor or spray mist. Keep out of reach of children. This material is electrically conductive. Do not apply by electrostatic spray equipment unless the equipment is modified and intended for the application of conductive coatings.

===== **SECTION VIII - CONTROL MEASURES** =====

**RESPIRATORY PROTECTION**

Observe the OSHA Respiratory Protection Standard (29 CFR 1910.134) for respirator selection and use. Selection of the most appropriate respirator will depend on the specific work environment and should be made only by a person familiar with the working conditions and with the benefits and limitations of respiratory protection products.

**VENTILATION**

Ventilation should dilute to below LBL and TLV to be considered adequate. All applications areas should be ventilated in accordance with the applicable regulations found in 29 CFR, Part 1910.

Respiratory protection should be provided in accordance with 29 CFR, Part 1910.134.

**PROTECTIVE GLOVES**

Recommended if skin contact is likely.

**EYE PROTECTION**

Chemical goggles or safety eyewear with splash shields is recommended.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Suitable barrier cremes, impervious clothing and boots are recommended to reduce repeated contact with material and limit contamination.

**WORK/HYGIENIC PRACTICES**

Wash hands with soap and water before eating or using the washroom. Smoke in smoking areas only. Remove and wash contaminated clothing before reuse.

===== **SECTION IX - REGULATORY AND ADDITIONAL HAZARDS INFORMATION** =====

Cobalt Compounds - IARC concludes there is inadequate evidence for the carcinogenicity of cobalt and cobalt compounds in humans and sufficient evidence for the carcinogenicity of cobalt and cobalt compounds in experimental animals. IARC's overall evaluation is that cobalt compounds are possibly carcinogenic to humans (Group 2B). (IARC Monographs VOL 52(1991) COBALT AND COBALT COMPOUNDS)

All components used in the manufacture of this product are listed in the TSCA inventory.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER NO GUARANTY OR WARRENTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION ABOVE.